NEWS 2023

Technical data

ARKOSLIGHT

Black Foster Custom Trimless
Black Foster Recessed 2x2
Shot Light S
Lens Light
Black Foster Micro Surface
Loop
Rec Slim & Micro
Yoru Spike
Minimal Track Trimless
Track 48V Indirect Light
Wiz 48V
Trimless Tool
Fit Surface 65 & 80
Fit 27 24V
Black Foster Recessed White
Minimal Track White
Line Micro 24V White
Line 48V White

BLACK FOSTER **Custom Trimless 1m**	**A458-01-00- | N |**
BLACK FOSTER **Custom Trimless 2m**	**A458-02-00- | N |**
BLACK FOSTER **Custom Trimless 3m**	**A458-03-00- | N |**



BLACK FOSTER **Custom Trimless**	**A458-04-00- | N |**

L-Joint



L

BLACK FOSTER **Custom Cover Gap 250**	**A452-00-01- | N |**	250mm
BLACK FOSTER **Custom Cover Gap 500**	**A452-00-02- | N |**	500mm



BLACK FOSTER **Custom Trimless**	**A458-05-00**

Plaster Installation Guard 1m





		P	V	D (A x B x C)
CONSTANT VOLTAGE LED POWER SUPPLY	**0434-01-61* | N |**	100W	48V	298 x 19 x 16mm
	0434-01-62	150W	48V	350 x 30 x 18mm

220 240 V~ | *To be installed inside the track.





DROP VOLTAGE TABLE

POWER (W)	CABLE SECTION (mm²)	CABLE LENGHT (m) 5	10	20	30
		TRACK LENGHT (m)			
100	0,75	50	50	X	X
	1,5	50	50	40	25
150	0,75	40	15	X	X
	1,5	50	40	20	X

COLOUR | N ■ |

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)

» PLEASE CONSULT

BLACK FOSTER **Custom Trimless End**

A458-00-01- | N |

Cover Thickness = 2 mm.

BLACK FOSTER **Custom Trimless End Feed**

A458-00-02- | N |

Cover Thickness = 2 mm.

BLACK FOSTER **Straight Joiner**

A317-00-06

Live-End Connector 48V

A338-00-01- | N |



L-Joint Connector 48V

A338-00-12- | N |



Central Connector 48V

A338-00-02- | N |



MOUNTING ACCESSORIES

Track Fixation Kit	**A219-21-06- | B |**
Track Flush Ceiling Kit	**A219-22-06- | B |**
Track Clamp Kit for M6 ROD	**A219-21-21- | B |**
Track Suspension Kit	**A219-21-10- | B |**



SUGGESTED MOUNTING ACCESSORIES QUANTITIES

1000 mm - 2 Pcs
2000 mm - 2 Pcs
3000 mm - 3 Pcs

COLOUR | N ■ | B □ |

>> MORE INFO

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED
BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)

>> MORE INFO

		P	CCT	I	Flux
BLACK FOSTER Custom Module 3	A453-3- ○ - ◎ -0- | N | NMG |	6,3W	2700K	700mA	570 lm
	A453-3- ○ - ◎ -1- | N | NMG |	6,3W	3000K	700mA	630 lm
	A453-3- ○ - ◎ -2- | N | NMG |	6,3W	4000K	700mA	750 lm
BLACK FOSTER Custom Module 5	A453-4- ○ - ◎ -0- | N | NMG |	10,5W	2700K	700mA	950 lm
	A453-4- ○ - ◎ -1- | N | NMG |	10,5W	3000K	700mA	1050 lm
	A453-4- ○ - ◎ -2- | N | NMG |	10,5W	4000K	700mA	1250 lm
BLACK FOSTER Custom Module 10	A453-5- ○ - ◎ -0- | N | NMG |	21W	2700K	700mA	1900 lm
	A453-5- ○ - ◎ -1- | N | NMG |	21W	3000K	700mA	2100 lm
	A453-5- ○ - ◎ -2- | N | NMG |	21W	4000K	700mA	2500 lm

48 V | III **IP**20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | UGR <19 | 38° / 19°

○	BEAM	LOR
0	38°	92%
1	19°	90%

◎	*OPTIONS
1	No DIM
2	DIM DALI



COLOUR | N ■ | NMG ■ | MATERIAL | AL | ABS+PC |

» PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux
BLACK FOSTER Custom Module FIT 27	A454-0- ◎ - ○ -0- | WT | NT | G |	5,5W	2700K	500mA	550 lm
	A454-0- ◎ - ○ -1- | WT | NT | G |	5,5W	3000K	500mA	600 lm
	A454-0- ◎ - ○ -2- | WT | NT | G |	5,5W	4000K	500mA	640 lm

48 V | III IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | OPTIONS* | INCL | 355° | 90° | 22° / 37° / 46°

○	BEAM	LOR
1	22°	84%
2	37°	82%
3	46°	81%

◎	*OPTIONS
1	No DIM
2	DIM DALI



COLOUR | WT □ | NT ■ | G ■ | MATERIAL | AL | PC |

» PLEASE CONSULT

THE INVISIBLE BLACK

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
BLACK FOSTER Recessed 1	A319-10- ⓪ -0- | N | W | WN | NMG |	2,1W	2700K	38°	700mA	190 lm	92%
	A319-10- ⓪ -1- | N | W | WN | NMG |	2,1W	3000K	38°	700mA	210 lm	92%
	A319-10- ⓪ -2- | N | W | WN | NMG |	2,1W	4000K	38°	700mA	250 lm	92%
	A319-11- ⓪ -0- | N | WN | NMG |	2,1W	2700K	19°	700mA	190 lm	90%
	A319-11- ⓪ -1- | N | WN | NMG |	2,1W	3000K	19°	700mA	210 lm	90%
	A319-11- ⓪ -2- | N | WN | NMG |	2,1W	4000K	19°	700mA	250 lm	90%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | INCL | 50 X 50 | UGR <19 | 38° / 19°

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
BLACK FOSTER Recessed 2	A319-20- ⓪ -0- | N | W | WN | NMG |	4,2W	2700K	38°	700mA	380 lm	92%
	A319-20- ⓪ -1- | N | W | WN | NMG |	4,2W	3000K	38°	700mA	420 lm	92%
	A319-20- ⓪ -2- | N | W | WN | NMG |	4,2W	4000K	38°	700mA	500 lm	92%
	A319-21- ⓪ -0- | N | WN | NMG |	4,2W	2700K	19°	700mA	380 lm	90%
	A319-21- ⓪ -1- | N | WN | NMG |	4,2W	3000K	19°	700mA	420 lm	90%
	A319-21- ⓪ -2- | N | WN | NMG |	4,2W	4000K	19°	700mA	500 lm	90%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 93 | UGR <19 | 38° / 19°

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
BLACK FOSTER Recessed 3	A319-30- ⓪ -0- | N | W | WN | NMG |	6,3W	2700K	38°	700mA	570 lm	92%
	A319-30- ⓪ -1- | N | W | WN | NMG |	6,3W	3000K	38°	700mA	630 lm	92%
	A319-30- ⓪ -2- | N | W | WN | NMG |	6,3W	4000K	38°	700mA	750 lm	92%
	A319-31- ⓪ -0- | N | WN | NMG |	6,3W	2700K	19°	700mA	570 lm	90%
	A319-31- ⓪ -1- | N | WN | NMG |	6,3W	3000K	19°	700mA	630 lm	90%
	A319-31- ⓪ -2- | N | WN | NMG |	6,3W	4000K	19°	700mA	750 lm	90%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 136 | UGR <19 | 38° / 19°

⓪	*OPTIONS
1	No DIM
2	DIM Push
4	DIM DALI

DIM PHASE CUT PLEASE CONSULT



COLOUR | N ■ | W □ | WN ■□ | NMG ■■ | MATERIAL | AL | ABS+PC |

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, WN & NMG COLOURS

& » PLEASE CONSULT

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
BLACK FOSTER Recessed 5	A319-40- ⓪ -0- | N | W | WN | NMG |	10,5W	2700K	38°	700mA	950 lm	92%
	A319-40- ⓪ -1- | N | W | WN | NMG |	10,5W	3000K	38°	700mA	1050 lm	92%
	A319-40- ⓪ -2- | N | W | WN | NMG |	10,5W	4000K	38°	700mA	1250 lm	92%
	A319-41- ⓪ -0- | N | WN | NMG |	10,5W	2700K	19°	700mA	950 lm	90%
	A319-41- ⓪ -1- | N | WN | NMG |	10,5W	3000K	19°	700mA	1050 lm	90%
	A319-41- ⓪ -2- | N | WN | NMG |	10,5W	4000K	19°	700mA	1250 lm	90%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 222 | UGR <19 | 38° / 19°

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
BLACK FOSTER Recessed 2x2	A319-50- ⓪ -0- | N | W | WN |	8,4W	2700K	38°	700mA	760 lm	92%
	A319-50- ⓪ -1- | N | W | WN |	8,4W	3000K	38°	700mA	840 lm	92%
	A319-50- ⓪ -2- | N | W | WN |	8,4W	4000K	38°	700mA	1000 lm	92%
	A319-51- ⓪ -0- | N | WN |	8,4W	2700K	19°	700mA	760 lm	90%
	A319-51- ⓪ -1- | N | WN |	8,4W	3000K	19°	700mA	840 lm	90%
	A319-51- ⓪ -2- | N | WN |	8,4W	4000K	19°	700mA	1000 lm	90%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 93 X 93 | UGR <19 | 38° / 19°

⓪	*OPTIONS
1	No DIM
2	DIM Push
4	DIM DALI

DIM PHASE CUT PLEASE CONSULT



COLOUR | N | W | WN | NMG |

MATERIAL | AL | ABS+PC |

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, WN & NMG COLOURS

& » PLEASE CONSULT

THE INVISIBLE BLACK

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
SHOT LIGHT S	A462-0- ⓪ -00- | N | NMG | WMG |	6W	2700K	18°	500mA	640 lm	89%
	A462-0- ⓪ -01- | N | NMG | WMG |	6W	3000K	18°	500mA	670 lm	89%
	A462-0- ⓪ -02- | N | NMG | WMG |	6W	4000K	18°	500mA	720 lm	89%
	A462-0- ⓪ -10- | N | NMG | WMG |	6W	2700K	40°	500mA	640 lm	89%
	A462-0- ⓪ -11- | N | NMG | WMG |	6W	3000K	40°	500mA	670 lm	89%
	A462-0- ⓪ -12- | N | NMG | WMG |	6W	4000K	40°	500mA	720 lm	89%

220 240 V~ | IP20 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 2 | OPTIONS* | INCL | Ø55 | 18° / 40°

	P	CCT	Beam	I	Flux	LOR
SHOT LIGHT S IP65	A462-1- ⓪ -10- | N | W | NMG | WMG |	5W	2700K	40°	500mA	640 lm	84%
	A462-1- ⓪ -11- | N | W | NMG | WMG |	5W	3000K	40°	500mA	670 lm	84%
	A462-1- ⓪ -12- | N | W | NMG | WMG |	5W	4000K	40°	500mA	720 lm	84%

220 240 V~ | IP65 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 2 | OPTIONS* | INCL | Ø55 | 40°

⓪	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push

DIM PHASE CUT PLEASE CONSULT



COLOUR | N | W | NMG | WMG |

MATERIAL | AL | ABS+PC |

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, NMG & WMG COLOURS

& » PLEASE CONSULT

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
SHOT LIGHT S Trimless	A463-0- ◎ -00- | N | NMG |	6W	2700K	18°	500mA	640 lm	89%
	A463-0- ◎ -01- | N | NMG |	6W	3000K	18°	500mA	670 lm	89%
	A463-0- ◎ -02- | N | NMG |	6W	4000K	18°	500mA	720 lm	89%
	A463-0- ◎ -10- | N | W | NMG |	6W	2700K	40°	500mA	640 lm	89%
	A463-0- ◎ -11- | N | W | NMG |	6W	3000K	40°	500mA	670 lm	89%
	A463-0- ◎ -12- | N | W | NMG |	6W	4000K	40°	500mA	720 lm	89%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | EXCL** | OPTIONS* | INCL | Ø59 | 18° / 40°

◎	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push

DIM PHASE CUT PLEASE CONSULT

ACCESSORY

SHOT LIGHT S Trimless Accessory** A463-00-00

** MANDATORY FOR INSTALLATION

Ø59







COLOUR | N ■ | W □ | NMG ■ | MATERIAL | AL | ABS+PC |

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N & NMG COLOURS

& » PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
LENS LIGHT	**A469-0- ◎ -00- | N | W |**	5,7W	2700K	500mA	510 lm	89%
	A469-0- ◎ -01- | N | W |	5,7W	3000K	500mA	540 lm	89%
	A469-0- ◎ -02- | N | W |	5,7W	4000K	500mA	580 lm	89%

220 240 V~ | □ **IP**20 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 2 | OPTIONS* | INCL | Ø38 | 11°

◎	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push



COLOUR | N ■ | W □ | MATERIAL | AL | ABS+PC |

*OTHER DIM OPTIONS PLEASE CONSULT
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

& » PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
LENS LIGHT **Trimless**	**A470-0-** ⓞⓞ **-00-** | **N** | **W** |	5,7W	2700K	500mA	510 lm	89%
	A470-0- ⓞⓞ **-01-** | **N** | **W** |	5,7W	3000K	500mA	540 lm	89%
	A470-0- ⓞⓞ **-02-** | **N** | **W** |	5,7W	4000K	500mA	580 lm	89%

220 240 V~ | **IP**20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | EXCL** | OPTIONS* | INCL | Ø43 | 11°

ⓞⓞ	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push

ACCESSORY

LENS LIGHT **Trimless Accessory****	**A470-00-00**

** MANDATORY FOR INSTALLATION

Ø43







COLOUR | **N** ■ | **W** □ | MATERIAL | **AL** | **ABS+PC** |

*OTHER DIM OPTIONS PLEASE CONSULT
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

& » PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER MICRO Surface 5	A459-20-00- | NT | WT |	7W	2700K	500mA	775 lm	87%
	A459-20-01- | NT | WT |	7W	3000K	500mA	800 lm	87%
	A459-20-02- | NT | WT |	7W	4000K	500mA	850 lm	87%

IP20 | CRI>90 | L90B10 >60.000 h

MacAdam Step 3 | OPTIONS* | EXCL | 37°

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER MICRO Surface 2x2	A459-30-00- | NT | WT |	5,6W	2700K	500mA	620 lm	87%
	A459-30-01- | NT | WT |	5,6W	3000K	500mA	640 lm	87%
	A459-30-02- | NT | WT |	5,6W	4000K	500mA	680 lm	87%

IP20 | CRI>90 | L90B10 >60.000 h

MacAdam Step 3 | OPTIONS* | EXCL | 37°

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER MICRO Surface 3x3	A459-40-00- | NT | WT |	10W	2700K	400mA	1170 lm	87%
	A459-40-01- | NT | WT |	10W	3000K	400mA	1200 lm	87%
	A459-40-02- | NT | WT |	10W	4000K	400mA	1300 lm	87%

IP20 | CRI>90 | L90B10 >60.000 h

MacAdam Step 3 | OPTIONS* | EXCL | 37°

*DRIVER OPTIONS		Black Foster Micro Surface 5	Black Foster Micro Surface 2x2	Black Foster Micro Surface 3x3
ON/OFF	0434-00-42	1 to 2	1 to 3	
	0434-01-53			1
DALI	0434-00-44	1 to 3	1 to 3	
	0434-01-54			1

220 240 V~ | DRIVER MUST BE PLACED ON REMOTE



COLOUR | NT ■ | WT □ | MATERIAL | AL | ABS+PC |

* OTHER DIM OPTIONS PLEASE CONSULT

» PLEASE CONSULT

SMEG

>> MORE INFO

	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push

FINISHING **

Lamp	Cable	Base
N ■	N ■	NT ■
BG ■	N ■	NT ■

		P	CCT	I	Flux	LOR
LOOP	A473-10- ⓞⓞ -0- | N | BG |	26,5W	2700K	700mA	2800 lm	38%
	A473-10- ⓞⓞ -1- | N | BG |	26,5W	3000K	700mA	3060 lm	38%
220 240 V~ | □ IP20 | CRI>90 | L80B10 >60.000 h				MacAdam Step 3 / INCL / OPTIONS* / Ø62 / 110°		
LOOP Base	A473-20- ⓞⓞ -0- | N | BG |	26,5W	2700K	700mA	2800 lm	38%
	A473-20- ⓞⓞ -1- | N | BG |	26,5W	3000K	700mA	3060 lm	38%
220 240 V~ | □ IP20 | CRI>90 | L80B10 >60.000 h				MacAdam Step 3 / INCL / OPTIONS* / 110°		
LOOP Indirect	A474-10- ⓞⓞ -0- | N | BG |	26,5W	2700K	700mA	2800 lm	38%
	A474-10- ⓞⓞ -1- | N | BG |	26,5W	3000K	700mA	3060 lm	38%
220 240 V~ | □ IP20 | CRI>90 | L80B10 >60.000 h				MacAdam Step 3 / INCL / OPTIONS* / Ø62 / 110°		
LOOP Indirect Base	A474-20- ⓞⓞ -0- | N | BG |	26,5W	2700K	700mA	2800 lm	38%
	A474-20- ⓞⓞ -1- | N | BG |	26,5W	3000K	700mA	3060 lm	38%
220 240 V~ | □ IP20 | CRI>90 | L80B10 >60.000 h				MacAdam Step 3 / INCL / OPTIONS* / 110°		

LOOP / LOOP Indirect



LOOP Base / LOOP Indirect Base



COLOUR | N ■ | NT ■ | BG ■ | MATERIAL | OPTICAL GLASS | OPTICAL PMMA | AL | ABS +PC |

* OTHER DIM OPTIONS | ** OTHER FINISHING COMBINATIONS » PLEASE CONSULT

» PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
REC **Slim**	**A457-00-** ⓞⓞ **-0-** | **WT** | **NT** | **PR** |	27W	2700K	700mA	3700 lm	86%
	A457-00- ⓞⓞ **-1-** | **WT** | **NT** | **PR** |	27W	3000K	700mA	3800 lm	86%
	A457-00- ⓞⓞ **-2-** | **WT** | **NT** | **PR** |	27W	4000K	700mA	4000 lm	86%

220 240 V~ | □ **IP**20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | OPTIONS* | INCL | 97°

ⓞⓞ	*OPTIONS
1	No DIM
2	DIM DALI
3	DIM Push

>> MORE INFO

		CCT	LOR
REC **Micro**	**A461-00-00-** | **WT** | **NT** | **PR** |	2700K	79%
	A461-00-01- | **WT** | **NT** | **PR** |	3000K	79%
	A461-00-02- | **WT** | **NT** | **PR** |	4000K	79%

III **IP**20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | OPTIONS* | EXCL** | 97°

*DRIVER OPTIONS		P	I	CCT	Flux
NO DIM	**0434-00-40** 1 to 2 Rec Micro	12,8W	700mA	2700K	1465 lm
				3000K	1560 lm
				4000K	1650 lm
	0434-01-43 1 to 3 Rec Micro	12,8W	700mA	2700K	1465 lm
				3000K	1560 lm
				4000K	1650 lm
DALI	**0434-00-46** 1 to 2 Rec Micro	12,8W	700mA	2700K	1465 lm
				3000K	1560 lm
				4000K	1650 lm
	0434-01-25 1 to 3 Rec Micro	12,8W	700mA	2700K	1465 lm
				3000K	1560 lm
				4000K	1650 lm

220 240 V~ | DRIVER MUST BE PLACED ON REMOTE

REC Slim



REC Micro



COLOUR | **WT** □ | **NT** ■ | **PR** ▮ | MATERIAL | **AL** | **PMMA** |

PR: PRIMER COATING FINISHING

» PLEASE CONSULT

>> MORE INFO

		P	CCT	Flux	LOR
YORU **Spike 24V**	**A475-** ⓞⓞ **-0 - 00-** | **WT** | **NT** |	3W	2700K	400 lm	84%
	A475- ⓞⓞ **-0 - 01-** | **WT** | **NT** |	3W	3000K	410 lm	84%

24 V | III **IP**65 | CRI>90 | L80B10 >60.000 h

OUTDOOR | MacAdam Step 2 | OPTIONS* | EXCL** | 100°

ⓞⓞ	TOTAL HEIGHT - H
1	400 mm
2	500 mm



OPTIONAL ACCESSORY

Connector IP67	**0434-01-67** | **N** |	
Connector IP67 T-Shape	**0434-01-68** | **N** |	

For cable Ø3,5-7,5mm, section <1,5mm²



			P	V	D (A x B x C)
YORU **Spike 24V** ** Remote Power Supply	ON/OFF	**0434-01-37**	60W	24V	180 x 52 x 30mm
		0433-10-22	100W	24V	295 x 43 x 30mm

220 240 V~ | **IP**20



YORU **Spike 24V** * Remote Constant Voltage Dimmer		**0433-01-32**	DALI / Push	24V	181 x 42 x 20mm
		0433-01-33	CASAMBI	24V	172 x 42 x 20mm
		0434-01-64	WIFI	24V	105 x 44 x 23mm

24 V | **IP**20



DROP VOLTAGE TABLE

POWER (W)	**CABLE SECTION** (mm²)	**CABLE LENGHT** (m) <25	<50	<75	<100
60	0,75	√	√	X	X
	1,5	√	√	√	√
100	0,75	√	X	X	X
	1,5	√	√	√	X

COLOUR | **WT** □ | **NT** ■ | MATERIAL | **INOX AISI 304** | **AL** | **PC** |

MINIMAL TRACK TRIMLESS

>> MORE INFO

INSTALLATION GUIDE
https://youtu.be/KnedJbKp7oo





MINIMAL TRACK 24V **Trimless**
Profile 2m **A467-02-00- | N |**

MINIMAL TRACK 24V **Trimless**
Rubber Cable n x 1m **A467-00-01- | N |**
n = Total Lenght of System.

24 V | Max. 4A | III

MINIMAL TRACK 24V **Trimless**
Corner 90º 1 Plane
A467-00-02- | N |
Cable Lenght = 140mm.



MINIMAL TRACK 24V **Trimless**
End Caps
A467-00-05- | N |
Two End Caps Included

MINIMAL TRACK 24V **Trimless**
Corner 90º 1 Plane Connector
A467-00-03- | N |



MINIMAL TRACK 24V **Trimless**
Straight Joiner
A467-00-06

MINIMAL TRACK 24V **Trimless**
Corner 90º 2 Planes
A467-00-04- | N |
Cable Lenght = 200mm.



MINIMAL TRACK 24V **Trimless**
Connection Box
A467-00-07- | N |



			P	V	D (A x B x C)
MINIMAL TRACK 24V **Remote Power Supply**	ON/OFF	**0434-01-37**	60W	24V	180 x 52 x 30mm
		0433-10-22	100W	24V	295 x 43 x 30mm

220 240 V~



MINIMAL TRACK 24V **Remote Constant Voltage Dimmer**		**0433-01-32**	DALI / Push	24V	181 x 42 x 20mm
		0433-01-33	CASAMBI	24V	172 x 42 x 20mm
		0434-01-64	WIFI	24V	105 x 44 x 23mm

24 V



DROP VOLTAGE TABLE

POWER (W)	CABLE SECTION (mm²)	CABLE LENGHT (m) <5	<10	<20	<30
		TRACK LENGHT (m)			
60	0,75	30	30	20	10
	1,5	30	30	30	20
100	0,75	20	10	X	X
	1,5	20	20	10	X

Reduce 5 meters per each 'Corner 90º 1 Plane CONNECTOR' used.





COLOUR | N ■ |

DIM OPTIONS PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER Micro 24V Surface 5	A468-20-10- | NT | WT |	7W	2700K	500mA	775 lm	87%
	A468-20-11- | NT | WT |	7W	3000K	500mA	800 lm	87%
	A468-20-12- | NT | WT |	7W	4000K	500mA	850 lm	87%

24 V | III **IP**20 | CRI>90 | L90B10 >60.000 h

MacAdam Step 3 | INCL | MINIMAL TRACK | 37°



COLOUR | NT ■ | WT □ | MATERIAL | AL | ABS+PC |

» PLEASE CONSULT

>> MORE INFO

		P	CCT	Flux	LOR	L
TRACK 48V + IND. LIGHT 1400	A466-01-20- | NT | WT |	18,3W	2700K	2320lm	70%	1402mm
	A466-01-21- | WT | NT |	18,3W	3000K	2380lm	70%	1402mm
	A466-01-22- | WT | NT |	18,3W	4000K	2585lm	70%	1402mm
TRACK 48V + IND. LIGHT 2800	A466-02-20- | WT | NT |	39,2W	2700K	5210lm	70%	2802mm
	A466-02-21- | WT | NT |	39,2W	3000K	5360lm	70%	2802mm
	A466-02-22- | WT | NT |	39,2W	4000K	5820lm	70%	2802mm

48 V | III | IP20 | CRI>90 | L90B5 >50.000 h

MacAdam Step 3 | DALI | EXCL | 106°

TRACK 48V + INDIRECT LIGHT
1400 / 2800





Indirect Light Suspension kit 48V (2 units)

A466-00-03- | NT | WT |



Suspension straight joiner kit 48V

A466-00-04- | NT | WT |



Suspension 90º Corner joiner kit 48V

A466-00-05- | NT | WT |

III

*Electrical connection not included.

DROP VOLTAGE TABLE

		CABLE LENGHT (m)			
		5	10	20	30
POWER (W)	CABLE SECTION (mm^2)	TRACK LENGHT (m)			
100	0,75	50	50	X	X
	1,5	50	50	40	25
150	0,75	40	15	X	X
	1,5	50	40	20	X

For calculations, you must consider indirect light power.

		P	V	D (A x B x C)
CONSTANT VOLTAGE LED POWER SUPPLY	0434-01-61*| N | W |	100W	48V	298 x 19 x 16mm
	0434-01-62	150W	48V	350 x 30 x 18mm

220 240 V~ | *To be installed inside the track.





COLOUR | NT ■ | N ■ | WT □ | MATERIAL | AL | PC |

» PLEASE CONSULT



Live-End Connector 48V

A338-00-01- | N | W |



L-JOINT Connector 48V

A338-00-12- | N | W |



Corner 90º Connector One Plane 48V

A338-00-24- | N | W |

End 48V

A338-00-06- | NT | WT |



Wired Power Supply Case 48V

A338-00-25- | NT | WT | 150W NO DIM

A338-00-26- | NT | WT | 150W DIM

220 240 V~ INCL



Central Connector 48V

A338-00-02- | N | W |



Wireless Control 48V

0434-01-31- | N | W | Casambi/AAG Stucchi App



Cover Gap 1m 48V

A338-00-30- | N | W |

End Feed 48V

A338-00-07- | NT | WT |



Suspension Feed Kit

A338-00-16- | N | W | NO DIM

A338-00-17- | N | W | DIM

For remote power supply

A338-00-27- | N | W | NO DIM

A338-00-28- | N | W | DIM

For power supply inside the track

MAINS TRIMLESS

MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS

WIRE TRIMLESS ACCESSORIES

FEED

Mains Trimless*

A023-00-01- | W | N | NO DIM

Mains Thick Trimless*

A023-00-02- | W | N | DIM



FASTENING

Steel Cable Trimless*

A023-00-05- | W | N |

COLOUR | WT □ | NT ■ | W □ | N ■ | MATERIAL | AL | PC |

* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

» PLEASE CONSULT

48V SYSTEM

WIZ 48V

>> MORE INFO

WIZ **48V**	+RE	P	CCT	I	Flux	LOR
A465-0- ⓒ **-10-** | **WT** | **NT** | **WTW** | **NTW** |	-S	12,4W	2700K	350mA	1470 lm	86%
A465-0- ⓒ **-11-** | **WT** | **NT** | **WTW** | **NTW** |	-S	12,4W	3000K	350mA	1530 lm	86%
A465-0- ⓒ **-12-** | **WT** | **NT** | **WTW** | **NTW** |	-S	12,4W	4000K	350mA	1550 lm	86%

48 V | III **IP**20 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | UGR <19 | 38°

ⓒ	*OPTIONS
1	No DIM
2	DIM DALI

+RE	REF. ENDING	EXAMPLE
Ø	Track 48V	**A4650110WT**
-S	Track 48V Short	**A4650110WT-S**

OPTIONAL

WIZ **High Chromatic LED**

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS

FINISHING	Body	Lampshade	Adaptor
WT	**WT** ☐	**N** ■	**N** ■
NT	**NT** ■	**N** ■	**N** ■
WTW	**WT** ☐	**N** ■	**W** ☐
NTW	**NT** ■	**N** ■	**W** ☐

WIZ 48V



VISIBLE LIMIT

WIZ 48V SHORT (-S)



COLOUR | **WT** ☐ | **NT** ■ | **W** ☐ | **N** ■ | MATERIAL | **AL** | **ABS+PC** |

* OTHER DIM OPTIONS PLEASE CONSULT
+RE >> THE PRODUCTS FOR THE *TRACK 48V SHORT*, ADD "**-S**" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

» PLEASE CONSULT

ACCESSORY

TRIMLESS TOOL

>> MORE INFO

INSTALLATION GUIDE
https://youtu.be/sa_xAgj4ji4

OPTIONAL ACCESSORY

TRIMLESS TOOL D16 X D34mm A478-00-00



Suitable for:
Magnetic Connector | A435-01-00:
· FIT 20 | A431-00-XX
· FIT 27 | A432-01-XX
· iO Micro | A434-01-XX
· PLUS Micro | A433-01-XX
· SIX XS | A429-01-XX
· TOP Micro | A430-01-XX

OPTIONAL ACCESSORY

TRIMLESS TOOL D20 X D52mm A478-00-01



Suitable for:
Alaska Big | A455-XX-XX
Wire Trimless Accessory | A023-XX-XX:
· Acc. Mains Trimless | A023-00-01
· Acc. Mains Thick Trimless | A023-00-02
· Acc. Coaxial Trimless | A023-00-03
· Acc. Unipolar Trimless | A023-00-04
· Acc. Steel Cable Trimless | A023-00-05
· Acc. Steel Cable Regulator Trimless | A023-00-06

OPTIONAL ACCESSORY

TRIMLESS TOOL D43 X D704mm A478-00-02



Suitable for:
Alaska Trimless Accessory | A401-10-XX
Shot Light Trimless Accessory | A269-00-00
Shot Light Trimless Accessory 2 | A269-00-01
Shot Light Trimless Accessory 3 | A269-00-02
Lens Light Trimless Accessory | A470-00-00

OPTIONAL ACCESSORY

TRIMLESS TOOL D59 X D100mm A478-00-03



Suitable for:
Alaska Big Trimless Accessory | A426-10-00
Shot Light S Trimless Accessory | A463-00-00

OPTIONAL ACCESSORY

TRIMLESS TOOL D79 X D86mm A478-00-04



Suitable for:
Shot Light S Flex | A477-00-00

OPTIONAL ACCESSORY

TRIMLESS TOOL D79 X D120mm A478-00-05



Suitable for:
Shot Light M Trimless Accesory | A298-00-00

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
FIT **65** Surface	**A471-0-** ◌◌ **-11-** | **WT** | **NT** |	10,3W	3000K	18°	300mA	1300 lm	90%
	A471-0- ◌◌ **-12-** | **WT** | **NT** |	10,3W	4000K	18°	300mA	1320 lm	90%
	A471-0- ◌◌ **-21-** | **WT** | **NT** |	10,3W	3000K	26°	300mA	1300 lm	88%
	A471-0- ◌◌ **-22-** | **WT** | **NT** |	10,3W	4000K	26°	300mA	1320 lm	88%
	A471-0- ◌◌ **-31-** | **WT** | **NT** |	10,3W	3000K	36°	300mA	1300 lm	84%
	A471-0- ◌◌ **-32-** | **WT** | **NT** |	10,3W	4000K	36°	300mA	1320 lm	84%

220 240 V~ | **IP**20 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 2 | OPTIONS* | INCL | 350° | 90° | 18°/26°/36°

◌◌	*OPTIONS
1	No DIM
2	DIM DALI

OPTIONAL ACCESSORY

FIT 65 **Anti-glare Honeycomb Louver **** **A356-00-00**

NOT SOLD SEPARATELY



COLOUR | **WT** □ | **NT** ■ | MATERIAL | **AL** | **PC** |

** ACCESSORY AFFECTS THE LIGHTING PARAMETERS

» PLEASE CONSULT

>> MORE INFO

		P	CCT	Beam	I	Flux	LOR
FIT **80** Surface	**A472-0-** ◎◎ **-11-** | **WT** | **NT** |	19W	3000K	19°	550mA	2500 lm	90%
	A472-0- ◎◎ **-12-** | **WT** | **NT** |	19W	4000K	19°	550mA	2540 lm	90%
	A472-0- ◎◎ **-21-** | **WT** | **NT** |	19W	3000K	28°	550mA	2500 lm	84%
	A472-0- ◎◎ **-22-** | **WT** | **NT** |	19W	4000K	28°	550mA	2540 lm	84%
	A472-0- ◎◎ **-31-** | **WT** | **NT** |	19W	3000K	37°	550mA	2500 lm	85%
	A472-0- ◎◎ **-32-** | **WT** | **NT** |	19W	4000K	37°	550mA	2540 lm	85%

220 240 V~ | **IP**20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | OPTIONS* | INCL | 350° | 90° | 19°/28°/37°

◎◎	*OPTIONS
1	No DIM
2	DIM DALI

OPTIONAL ACCESSORY

FIT 80 **Anti-glare Honeycomb Louver **** **A357-00-00**

NOT SOLD SEPARATELY



COLOUR | **WT** □ | **NT** ■ | MATERIAL | **AL** | **PC** |

** ACCESSORY AFFECTS THE LIGHTING PARAMETERS

» PLEASE CONSULT

>> MORE INFO

		P	CCT	BEAM	I	Flux	LOR
FIT **27 24V 1**	**A399-00-10-** | **WT** | **NT** | **G** |	4,5W	2700K	22°	400mA	440 lm	84%
	A399-00-11- | **WT** | **NT** | **G** |	4,5W	3000K	22°	400mA	475 lm	84%
	A399-00-20- | **WT** | **NT** | **G** |	4,5W	2700K	37°	400mA	440 lm	82%
	A399-00-21- | **WT** | **NT** | **G** |	4,5W	3000K	37°	400mA	475 lm	82%
	A399-00-30- | **WT** | **NT** | **G** |	4,5W	2700K	46°	400mA	440 lm	81%
	A399-00-31- | **WT** | **NT** | **G** |	4,5W	3000K	46°	400mA	475 lm	81%
FIT **27 24V 2**	**A399-10-10-** | **WT** | **NT** | **G** |	5,5W	2700K	22°	500mA	550 lm	84%
	A399-10-11- | **WT** | **NT** | **G** |	5,5W	3000K	22°	500mA	600 lm	84%
	A399-10-20- | **WT** | **NT** | **G** |	5,5W	2700K	37°	500mA	550 lm	82%
	A399-10-21- | **WT** | **NT** | **G** |	5,5W	3000K	37°	500mA	600 lm	82%
	A399-10-30- | **WT** | **NT** | **G** |	5,5W	2700K	46°	500mA	550 lm	81%
	A399-10-31- | **WT** | **NT** | **G** |	5,5W	3000K	46°	500mA	600 lm	81%

24 V | III **IP**20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 2 | INCL | MINIMAL TRACK | 355° | 90° | 22° / 37° / 46°

FIT 27 24V



COLOUR | **WT** □ | **NT** ■ | **G** ■ | MATERIAL | **AL** | **PC** |

» PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER Recessed 1	A319-10- ⓪ -0- | N | W | WN | NMG |	2,1W	2700K	700mA	190 lm	92%
	A319-10- ⓪ -1- | N | W | WN | NMG |	2,1W	3000K	700mA	210 lm	92%
	A319-10- ⓪ -2- | N | W | WN | NMG |	2,1W	4000K	700mA	250 lm	92%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 50 | UGR <19 | 38°

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER Recessed 2	A319-20- ⓪ -0- | N | W | WN | NMG |	4,2W	2700K	700mA	380 lm	92%
	A319-20- ⓪ -1- | N | W | WN | NMG |	4,2W	3000K	700mA	420 lm	92%
	A319-20- ⓪ -2- | N | W | WN | NMG |	4,2W	4000K	700mA	500 lm	92%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 93 | UGR <19 | 38°

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER Recessed 3	A319-30- ⓪ -0- | N | W | WN | NMG |	6,3W	2700K	700mA	570 lm	92%
	A319-30- ⓪ -1- | N | W | WN | NMG |	6,3W	3000K	700mA	630 lm	92%
	A319-30- ⓪ -2- | N | W | WN | NMG |	6,3W	4000K	700mA	750 lm	92%

220 240 V~ | IP20 | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 136 | UGR <19 | 38°

>> MORE INFO

⓪	*OPTIONS
1	No DIM
2	DIM Push
4	DIM DALI

DIM PHASE CUT PLEASE CONSULT



COLOUR | N ■ | W □ | WN ■□ | NMG ■■ | MATERIAL | AL | ABS+PC |

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, WN & NMG COLOURS

& » PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER **Recessed 5**	**A319-40-** ⓪ **-0- | N | W | WN | NMG |**	10,5W	2700K	700mA	950 lm	92%
	A319-40- ⓪ **-1- | N | W | WN | NMG |**	10,5W	3000K	700mA	1050 lm	92%
	A319-40- ⓪ **-2- | N | W | WN | NMG |**	10,5W	4000K	700mA	1250 lm	92%

220 240 V~ | □ **IP20** | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 222 | UGR <19 | 38°

>> MORE INFO

		P	CCT	I	Flux	LOR
BLACK FOSTER **Recessed 2x2**	**A319-50-** ⓪ **-0- | N | W | WN |**	8,4W	2700K	700mA	760 lm	92%
	A319-50- ⓪ **-1- | N | W | WN |**	8,4W	3000K	700mA	840 lm	92%
	A319-50- ⓪ **-2- | N | W | WN |**	8,4W	4000K	700mA	1000 lm	92%

220 240 V~ | □ **IP20** | CRI>90 | L80B10 >60.000 h

MacAdam Step 3 | OPTIONS* | INCL | 93 X 93 | UGR <19 | 38°

⓪	*OPTIONS
1	No DIM
2	DIM Push
4	DIM DALI

DIM PHASE CUT PLEASE CONSULT



COLOUR | N ■ | W □ | WN ◧ | NMG ◧ | MATERIAL | AL | ABS+PC |

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, WN & NMG COLOURS

& » PLEASE CONSULT

ARKOSLIGHT

MINIMAL TRACK

>> MORE INFO

INSTALLATION GUIDE
https://youtu.be/KnedJbKp7oo



MINIMAL TRACK 24V Profile 2m — **A384-02-00- | N | WT |**



MINIMAL TRACK 24V Rubber Cable n x 1m — **A384-00-01- | N |**

n = Total Lenght of System.

24 V | Max. 4A

MINIMAL TRACK 24V Corner 90º 1 Plane
A384-00-02- | N | WT |
Cable Lenght = 35mm.



MINIMAL TRACK 24V Corner 90º 1 Plane Rounded
A384-00-03- | N | WT |
Cable Lenght = 35mm.



MINIMAL TRACK 24V Corner 90º 2 Planes
A384-00-04- | N | WT |
Cable Lenght = 100mm.



MINIMAL TRACK 24V End Cap
A384-00-05- | N | WT |

MINIMAL TRACK 24V Connection Box
A384-00-06- | N | WT |



			P	V	D (A x B x C)
MINIMAL TRACK 24V Power Supply Box	ON/OFF	**A384-00-07- | NT | WT |**	40W	24V	280 x 30 x 24mm
		A384-00-08- | NT | WT |	100W	24V	280 x 30 x 24mm

220 240 V~ | Included ON/OFF 24Vdc Power Supply.



MINIMAL TRACK 24V Remote Power Supply	ON/OFF	**0434-01-37**	60W	24V	180 x 52 x 30mm
		0433-10-22	100W	24V	295 x 43 x 30mm

220 240 V~



MINIMAL TRACK 24V Remote Constant Voltage Dimmer		**0433-01-32**	DALI / Push	24V	181 x 42 x 20mm
		0433-01-33	CASAMBI	24V	172 x 42 x 20mm
		0434-01-64	WIFI	24V	105 x 44 x 23mm

24 V



DROP VOLTAGE TABLE

POWER (W)	CABLE SECTION (mm²)	CABLE LENGHT (m) <5	<10	<20	<30
		TRACK LENGHT (m)			
40	0,75	30	30	30	30
	1,5	30	30	30	30
60	0,75	30	30	20	10
	1,5	30	30	30	20
100	0,75	20	10	X	X
	1,5	20	20	10	X





COLOUR | N ■ | NT ■ | WT □ |

DIM OPTIONS PLEASE CONSULT

MINIMAL TRACK SUSPENSION

>> MORE INFO

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

Coaxial Trimless	A023-00-03- | W | N |

FASTENERS NOT AVAILABLE.

REMOTE INCL Ø20



COAXIAL TRIMLESS



MINIMAL TRACK 24V Suspension

Profile 2m

A384-02-00- | **N** | **WT** |

Profile 2m Initial feed kit

A400-02-10- | **N** | **WT** |

Profile 2m Middle feed kit*

A400-02-20- | **N** | **WT** |

* Unidirectional Middle Feed.



MINIMAL TRACK 24V Suspension **Corner 90°**

A400-00-03- | **N** | **WT** |

Cable Lenght = 85mm.





MINIMAL TRACK 24V Suspension

Rubber Cable n x 1m **A400-00-01-** | **N** |

n = Total Lenght of System.

24 V | Max. 4A

MINIMAL TRACK 24V Suspension **Straight Joiner**

A400-00-02- | **N** | **WT** |

MINIMAL TRACK 24V Suspension Kit

A400-02-04- | **N** | **WT** |

Max distance between suspension kits = 100 cm.



MINIMAL TRACK 24V Suspension **End Caps**

A400-00-05- | **N** | **WT** |

Two End Caps Included.

			P	V	D (A x B x C)
MINIMAL TRACK 24V Suspension Power Supply Box	ON/OFF	**A400-00-06-** | **NT** | **WT** |	40W	24V	280 x 30 x 36mm
		A400-00-07- | **NT** | **WT** |	100W	24V	280 x 30 x 36mm
220 240 V~ | Included ON/OFF 24Vdc Power Supply.					
MINIMAL TRACK 24V Remote Power Supply	ON/OFF	**0434-01-37**	60W	24V	180 x 52 x 30mm
		0433-10-22	100W	24V	295 x 43 x 30mm
220 240 V~					
MINIMAL TRACK 24V Remote Constant Voltage Dimmer		**0433-01-32**	DALI / Push	24V	181 x 42 x 20mm
		0433-01-33	CASAMBI	24V	172 x 42 x 20mm
		0434-01-64	WIFI	24V	105 x 44 x 23mm

24 V



DROP VOLTAGE TABLE

		CABLE LENGHT (m)			
		<5	<10	<20	<30
POWER (W)	**CABLE SECTION** (mm^2)	TRACK LENGHT (m)			
40	0,75	30	30	30	30
	1,5	30	30	30	30
60	0,75	30	30	20	10
	1,5	30	30	30	20
100	0,75	20	10	X	X
	1,5	20	20	10	X





COLOUR | **N** ■ | **NT** ■ | **WT** □ |

RAL ⓘ » 538

DIM OPTIONS PLEASE CONSULT

>> MORE INFO

		P	CCT	I	Flux	LOR
LINE **Micro 250 24V**	**A395-00-00-** | **N** | **WT** |	2W	2700K	400mA	330 lm	70%
	A395-00-01- | **N** | **WT** |	2W	3000K	400mA	340 lm	70%
LINE **Micro 500 24V**	**A395-10-00-** | **N** | **WT** |	5W	2700K	400mA	820 lm	70%
	A395-10-01- | **N** | **WT** |	5W	3000K	400mA	840 lm	70%
LINE **Micro 1000 24V**	**A395-20-00-** | **N** | **WT** |	9W	2700K	700mA	1430 lm	70%
	A395-20-01- | **N** | **WT** |	9W	3000K	700mA	1500 lm	70%

24 V | III **IP**20 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 2 | INCL | MINIMAL TRACK | 113°

LINE MICRO 250 24V



LINE MICRO 500 24V



LINE MICRO 1000 24V



COLOUR | **N** ■ | **WT** □ | MATERIAL | **AL** | **PC** |

NOT VALID FOR MINIMAL TRACK 24V TRIMLESS
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

» PLEASE CONSULT

LINE 48V

>> MORE INFO

		P	CCT	I	Flux	LOR
LINE **500 48V**	**A376-10- ⓓ -0- | N | WT |**	10,5W	2700K	350mA	1500 lm	65%
	A376-10- ⓓ -1- | N | WT |	10,5W	3000K	350mA	1600 lm	65%
	A376-10- ⓓ -2- | N | WT |	10,5W	4000K	350mA	1650 lm	65%
LINE **1000 48V**	**A376-20- ⓓ -0- | N | WT |**	21W	2700K	700mA	3000 lm	65%
	A376-20- ⓓ -1- | N | WT |	21W	3000K	700mA	3200 lm	65%
	A376-20- ⓓ -2- | N | WT |	21W	4000K	700mA	3300 lm	65%
LINE **2000 48V**	**A376-30- ⓓ -0- | N | WT |**	42W	2700K	700mA	6000 lm	65%
	A376-30- ⓓ -1- | N | WT |	42W	3000K	700mA	6400 lm	65%
	A376-30- ⓓ -2- | N | WT |	42W	4000K	700mA	6600 lm	65%

48 V | III **IP**20 | CRI>90 | L80B10 > 60.000 h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 98°

ⓓ	*OPTIONS
1	No DIM
2	DIM DALI

LINE 500 48V



LINE 1000 48V



LINE 2000 48V



COLOUR | **N** ■ | **WT** □ | MATERIAL | **AL** | **PC** |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

» PLEASE CONSULT

Accessories

Driver options

FOR PRODUCTS WITH DRIVER EXCLUDED
220-240 VAC INPUT

		PIECES			
DIM	DRIVER	BLACK FOSTER MICRO SURFACE 5	BLACK FOSTER MICRO SURFACE 2X2	BLACK FOSTER MICRO SURFACE 3X3	REC MICRO
ON/OFF	D5			1	
	D6	1...2	1...3		
	D7				1...2
	D11				1...3
DALI	D23			1	
	D24	1...3	1...3		
	D25				1...2
	D28				1...3

CONSTANT CURRENT LED DRIVERS

DRIVER	TYPOLOGY	DIM	REFERENCE	DESCRIPTION	I
D5	A	ON/OFF	04340153	DRIVER PROFESSIONALE 42W CONFIG.400mA	400mA
D6	A		04340042	DRIVER PROFESSIONALE 42W CONFIG.500mA	500mA
D7	B		04340040	DRIVER PROFESSIONALE 42W CONFIG.700mA	700mA
D11	B		04340143	DRIVER MP50 K3 CONFIG.700mA	700mA
D23	D	DALI	04340154	DRIVER MAX.32W DIM DALI CONFIG 400mA	400mA
D24	D		04340044	DRIVER MAX.32W DIM DALI CONFIG 500mA	500mA
D25	E		04340046	DRIVER MAX.32W DIM DALI CONFIG 700mA	700mA
D28	E	DALI + PUSH + 1-10V	04340125	DRIVER MAXI JOLLY CONFIG 700mA	700mA

DRIVER MAXIMUM DISTANCE RANGE

DRIVER TYPOLOGY	A				B				C			
WIRE CROSS - SECTION	0,5mm²	1mm²	1,5mm²	2,5mm²	0,5mm²	1mm²	1,5mm²	2,5mm²	0,5mm²	1mm²	1,5mm²	2,5mm²
DISTANCE TO LED	20m	50m	50m	50m	10m	20m	20m	50m		10m	20m	30m

D				E				F				G			
0,5mm²	1mm²	1,5mm²	2,5mm²	0,5mm²	1mm²	1,5mm²	2,5mm²	0,5mm²	1mm²	1,5mm²	2,5mm²	0,5mm²	1mm²	1,5mm²	2,5mm²
15m	15m	15m	15m	10m	15m	15m	15m		10m	10m	15m	2m	2m	2m	2m

CONSTANT CURRENT LED DRIVER

				P (MAX)	I	D
ON/OFF			0434-01-53	18W	400mA	129 x 42 x 30mm
			0434-00-42	22W	500mA	
			0434-00-40	31W	700mA	
			0434-01-43	50W	700mA	124 x 79 x 22mm
DIM		DALI	0434-01-54	19W	400mA	103 x 67 x 21mm
			0434-00-44	24W	500mA	
			0434-00-46	32W	700mA	
		DALI | PUSH / 1-10V	0434-01-25	50W	700mA	124 x 79 x 22mm

Installation Schemes

PUSH: OPTION 1

1-10V



PHASE CUT

PUSH: OPTION 2

DALI



Connection Tips

SEVERAL FIXTURES CONNECTION TO A SINGLE CONSTANT CURRENT DRIVER







Trimless Mounting



Symbols

GLOSSARY

L	Longitud (en mm).	Length (in mm).	Longueur (en mm).	Lunghezza (in mm).	Länge (in mm).
AL	Aluminio	Aluminium	Aluminium	Alluminio	Aluminium
PC	Policarbonato	Polycarbonate	Polycabonate	Policarbonato	Polycarbonat
PE	Polietileno	Polyethylene	Polyéthylène	Poietilene	Polyäthylen
GL	Cristal	Glass	Verre	Vetro	Glas
PMMA	Polimetilmetacrilato	Polymethyl methacrylate	Polyméthacrylate de méthyle	Polimetilmetacrilato	Polymethylmetacrylat
INOX	Acero inoxidable	Stainless steel	Acier inoxidable	Acciaio inossidabile	Edelstahl
MATT	Mate	Matt	Opaque	Opaco	Matt
TRANS	Transparente	Transparent	Transparent	Trasparente	Transparent
ABS	Acrilonitrilo Butadieno Estireno	Acrylonitrile Butadiene Styrene	Acrylonitrile Butadiène Styrène	Acrilonitrile Butadiene Stirene	Acrylnitril-Butadien-Styrol
LOR	*Lumen Output Ratio.* Relación entre el flujo de salida de la luminaria y el flujo de salida de la fuente de luz.	Lumen Output Ratio. Ratio between the output flux of the luminaire and the output flux of the light source.	*Lumen Output Ratio.* Rapport entre le flux de sortie du luminaire et le flux de sortie de la source de lumière.	*Lumen Output Ratio.* Relazione tra il flusso di uscita dell'apparecchio e il flusso di uscita della sorgente luminosa.	Zusammenhang zwischen dem Ausgangsstrom der Leuchte und dem Ausgangsstrom der Lichtquelle.
IPXX	Índice de estanqueidad	Sealing rating	Indice d'étanchéité	Indice di sigillatura	Schutzgrad gegen Eindringen von Staub und Feuchtigkeit
IKXX	Índice de protección contra impactos	Impact resistance	Indice de protection contre des impacts	Indicizzi di protezione contro impatti	Stoßfestigkeitsgrad
MAX XX W	Potencia máxima	Maximum power	Puissance Maximum	Potenza massima	Maximale Leistung
CCT	Temperatura de color	Colour Temperature	Température de couleur	Temperatura di colore	Farbtemperatur
	Fabricado en	Made of	Fabriqué en	Fabbricato in	Hergestellt aus
	Reflector	Screen	Réflecteur	Riflettore	Reflektor
	Cristal óptico	Optical glass	Verre optique	Verro ottico	Optischem glas
	Difusor	Diffuser	Diffuseur	Diffusore	Diffusor
	Difusor	Diffuser	Diffuseur	Diffusore	Diffusor
	Lente refractora elíptica	Elliptical refractor	Réfracteur élliptique	Rifracttore ellittico	Linse (f. elliptischen Lichtkegel)
	Filtro panel de abeja	Honeycomb filter	Filtre nid d'abeilles	Filtri favo	Waben-Raster
	Pantalla asimétrica	Asymmetric screen	Accesoire asymetrique	Visiera asimetrica	Assymetrischer Schirm/Blende
	Difusor homogeneizador del haz de luz	Beam Mixer Diffuser	Diffuseur homogénéisateur de faisceau lumineux	Diffusore di fascio luminoso misto	Strahlenmischdiffusor
	Bisel extra	Add-on bezel	Collerette extra	Cornice extra	Zusatz-Zierring
	Certificado ENEC	ENEC certified	Certifié ENEC	Certificato ENEC	ENEC-Zertifizierung
	Certificado IEC	IEC certified	Certifié IEC	Certificato IEC	IEC-Zertifizierung
	Compatible con la normativa francesa RT2012 & BBC	Compatible with the French Standard RT2012 & BBC	Compatible avec la Norme française RT2012 & BBC	Compatibile con la normativa francese RT2012 & BBC	Kompatibel mit der französischen Norm RT2012 & BBC

	Clase I	Class I	Classe I	Classe I	Klasse I
	Clase II	Class II	Classe II	Classe II	Klasse II
	Clase III	Class III	Classe III	Classe III	Klasse III
12 V	Tensión de alimentación 12V	Input supply voltage 12V	Tension d'alimentation de l'ampoule 12V	Tensione di alimentazione della lampada 12V	Anschlussspannung 12V
24 V	Tensión de alimentación 24vdc	Power supply voltaje 24vdc	Tension d'alimentation de l'ampoule 24vdc	Tensione di alimentazione della lampada 24vdc	Netzspannung 24vdc
48 V	Tensión de alimentación 48vdc	Power supply voltaje 48vdc	Tension d'alimentation de l'ampoule 48vdc	Tensione di alimentazione della lampada 48vdc	Netzspannung 48vdc
220 240 V~	Tensión de alimentación 220-240V	Power supply voltaje 220-240V	Tension d'alimentation de l'ampoule 220-240V	Tensione di alimentazione della lampada 220-240V	Netzspannung 220-240V
EXCL	Equipo no incluido	Control gear not included	Équipement non inclus	Alimentatore non compreso	Vorschaltgerät exklusive
INCL	Equipo electrónico incluido	Electronic control gear included	Équipement électronique inclus	Alimentatore elettronico compreso	Vorschaltgerät elektronische inklusive
	Alojamiento en mm para empotrables	Fitting hole for recessed luminaires in mm	Espace d'emplacement en mm pour encastrables	Foro in mm ad incasso	Einbauloch in mm
	Empotrable cuadrado para agujero redondo	Squared fixture for round fitting holes	Encastrable carré pour trou rond	Quadrato da incasso per foro rotondo	Quadratische Leuchte mit rundem Einbauloch
	Ángulo de basculación	Tilting angle	Angle de basculation	Angolo di inclinazione	Drehwinkel - Kippwinkel
	Doble basculación	Double tilting actión	Double basculation	Doppia inclinazione	Doppelte Schwenkbarkeit
	Ángulo de giro	Rotation angle	Angle de rotation	Angolo di rotazione	Drehwinkel
FAST | CONNEC	Conexión rápida	Fast connection	Conexion rapide	Collegamento rapido	Schnellsteckeranschluss
EXCL	Bloque de conexión no incluido	Terminal strip not included	Bande terminale connector exclus	Morsetto non compreso	Ohne Klemmenleiste
	Conector USB-C	USB-C connector	Port USB-C	USB-C connect	USB-C Verbindungskabel
	Cargador universal	Universal charger	Chargeur universel	Caricatore universale	Universal-Ladegerät
	Conexión con enchufe	Plug-in	Connexion avec prise	Collegamento con spina	Anschluss mit Stecker
	Tipo de carril	Rail Type	Type de rail	Tipo de binario	Schienemodelle
	Regulable	Dimmable	Gradable	Dimmerabile	Dimmbar
CABLE	Longitud del cable	Cable length	Longueur de câble	Lunghezza di cavo	Hängekabel Schnelljustierungsvorrichtung
	Regulación rápida del cable de suspensión	Quick adjustment for cable suspension	Régulation rapide du câble de suspension	Regolazione rapida del cavo di sospensione	Schnelle Regulation del Hängekabels
	Control inalámbrico	Wireless control	Contrôle sans fil	Wireless control	Wireless control
	Dispositivo para alumbrado de emergencias	Emergency lighting device	Dispositif pour éclairage de secours	Dispositivo por iluminazione di emergenza	Notbeleuchtung
	Batería LI-ION	LI-ION battery	Batterie au lithium-ion	Batteria agli ioni di litio	Lithium-Ionen-Akku
	Tipo de instalación y dirección del haz de luz	Instalation type and light beam direction	Type d'installation et direction du faisceau lumineu	Tipo d'impianto e direzione del fascio	Art und Ausrichtung des Lichtkegels
	Confort visual. UGR *(Unified Glare Rating)*	UGR (Unified Glare Rating) Visual comfort	Confort visuel. UGR *(Unified Glare Rating)*	Comfort visivo. UGR *(Unified Glare Rating)*	Sehkomfort. UGR *(Unified Glare Rating)*
	Estabilidad cromática: Pasos MacAdam	Chromatic stability: MacAdam Steps	Stabilité chromatique: Pas MacAdam	Stabilità cromatica: Step MacAdam	Farbstabilität: MacAdam Stufen
	Carga máxima soportada	Maximum supported load	Charge maximale supportée	Carico massimo supportato	Maximale Traglast
	Temperatura máxima en supeficie	Maximum surface temperature	Température Maximale sur une surface	Temperatura massima in superficie	Maximale Temperatur an der Oberfläche
OUTDOOR	Válido para exterior	Suitable for outdoor use	Agréé pour l'extérieur	Adatto per uso esterno	Geeignet für Ausseninstallation
INDOOR	Para uso interior	Indoor luminaire	Pour usage en intérieur	Per uso interno	Innenleuchte

Colours

The lighting values indicated for each ref.code correspond to the results obtained from the tests carried out on the first mentioned colour of the list.

B | White

WT | Textured White

W | Matt White

WN | White-Black

NT | Textured Black

N | Matt Black

NMG | Matt black - Metallized gold

WMG | Matt White - Metallized gold

G | Gold

BG | Brushed Gold

PR | Primer Coating Finishing

BLACK FOSTER

N = RAL 9005
NMG = RAL not available. Metallic finish
NT = RAL 9005
NTMG = RAL not available. Metallic finish
W = Colour in the mass looks alike RAL 9016
WN = Colour in the mass looks alike RAL 9016 & RAL 9005
WT = RAL 9016
WTMG = RAL 9005 not available. Metallic finish

FIT

WT = RAL 9016
NT = RAL 9005
G = RAL not available. Paint of metallic nanoparticles

LENS LIGHT

N = RAL 9005
W = RAL 9016

LINE

WT = RAL 9016
NT = RAL 9005
N = Anodised, bath colour, looks alike RAL 9005
W = Anodised, bath colour, looks alike RAL 9016

LOOP

BG = RAL not available. Electrolytic bath
N = RAL 9005
NT = RAL 9005

MINIMAL TRACK

N = RAL 9005
WT = RAL 9016

REC

WT = RAL 9016
NT = RAL 9005
PR = Primer coating finish

SHOT LIGHT

N = Colour in the mass looks alike RAL 9005
NMG = RAL not available. Metallic finish
W = Colour in the mass looks alike RAL 9016
WMG = RAL not available. Metallic finish

TRACK 48V

N = RAL 9005
NT = RAL 9005
WT = RAL 9016

WIZ

WT = RAL 9016
NT = RAL 9005
N = Anodised, bath colour, looks alike RAL 9005
W = Anodised, bath colour, looks alike RAL 9016

YORU

WT = RAL 9016
NT = RAL 9005

Reference

INDEX

0433-01-32	21, 22, 37, 39
0433-01-33	21, 22, 37, 39
0433-10-22	21, 22, 37, 39
0434-00-40	19, 44
0434-00-42	15, 44
0434-00-44	15, 44
0434-00-46	19, 44
0434-01-25	19, 44
0434-01-31	25
0434-01-37	21, 22, 37, 39
0434-01-43	19, 44
0434-01-53	15, 44
0434-01-54	15, 44
0434-01-61	4, 24
0434-01-62	4, 24
0434-01-64	21, 22, 37, 39
0434-01-67	21
A023-00-01	25
A023-00-02	25
A023-00-03	38
A023-00-05	25
A219-21-06	5
A219-21-10	5
A219-21-21	5
A219-22-06	5
A317-00-06	5
A319-1X-XX	8, 34
A319-2X-XX	8, 34
A319-3X-XX	8, 34
A319-4X-XX	9, 35
A319-5X-XX	9, 35
A338-00-0X	5, 25
A338-00-1X	5, 25
A338-00-2X	25
A338-00-30	25
A356-00-00	30
A357-00-00	31
A376-10-X-0	41
A376-10-XX	41
A376-20-XX	41
A376-30-XX	41
A384-00-0X	37
A384-02-00	37, 39
A395-00-0X	40
A395-10-0X	40
A395-20-0X	40
A399-00-XX	32
A400-00-XX	39
A400-02-XX	39
A452-00-0X	4
A453-3X-XX	6
A453-4X-XX	6
A453-5X-XX	6
A454-0X-XX	7
A457-00-XX	19
A458-00-0X	5
A458-0X-00	4
A459-20-0X	15
A459-30-0X	15
A459-40-0X	15
A461-00-0X	19
A462-0X-XX	10
A463-0X-XX	11
A465-0X-1X	27
A466-0X-XX	24
A467-00-0X	22
A467-02-00	22
A468-20-1X	23
A469-0X-0X	12
A470-0X-0X	13
A471-0X-XX	30
A472-0X-XX	31
A473-10-XX	17
A473-20-XX	17
A474-10-XX	17
A474-20-XX	17
A475-X0-0X	21
A478-00-0X	29

CEILING RECESSED

BLACK FOSTER MICRO

BLACK FOSTER

SHOT LIGHT

LENS LIGHT

SWAP

POINTER

LEX


ALASKA TRIMLESS


PUCK RECESSED

DUOMO

OLYMPIA

DEEP

DROP

STRAM


FOX


MIX

MADISON

QUAD

ESSENTIALS

POP UP

HIDDEN

TWIST

ORBITAL

WELLIT


HUBBLE

MAGNETIC PLUS MICRO


MAGNETIC FIT

MAGNETIC SIX XS

MAGNETIC iO MICRO


MAGNETIC TOP MICRO

SIX RECESSED

FIT RECESSED


PLUS RECESSED

SURFACE

BLACK FOSTER MICRO SURFACE

BLACK FOSTER SURFACE

SHOT LIGHT M SURFACE

TOP

SCOPE SURFACE

PUCK

ORBITAL SURFACE


VOLA

SKY

STRAM SURFACE

DRUM

FIFTY+ SURFACE

FIT SURFACE

iO SURFACE

ZEN TUBE SURFACE

SUSPENSION

ALASKA

ART

STICK

HOLLY

SPIN

SCOPE

VOLA SUSPENSION

SALT

BRIGIT

DRUM SUSPENSION

LOOP

LINE SUSPENSION

BLACK FOSTER SUSPENSION

SLIMGOT

FIFTY+ SUSPENSION

WALL, FLOOR & PORTABLE

UP

YORU

REC

LIP

FLAP

AURAE


DREAM

RHINO

WALLY

ALFA

YORU SPIKE

DARK


STEP

TRACK LIGHTS

MINIMAL TRACK

BLACK FOSTER MICRO 24V

ALASKA 24V

PLUS MICRO 24V


SIX XS 24V

TOP MICRO 24V

LINE MICRO 24V

iO MICRO 24V

FIT 24V

STICK 22 24V

TRACK 48V

SIX 48V

FIT 48V

PLUS 48V


iO 48V

ZEN TUBE 48V

WIZ 48V

TOP 48V

LINE 48V

BLACK FOSTER MICRO 48V

STICK 48V

HOLLY 48V

SPIN 48V

TRACK 1L

iO

PLUS MINI 1L

FIT 65 1L

TRACK 3L

SIX


FIT

PLUS

ZEN


ZEN TUBE

THOR

CUSTOM SYSTEMS

FANCY SHAPE

TOP FANCY SHAPE


ALASKA FANCY SHAPE

STICK FANCY SHAPE

SPIN FANCY SHAPE

HOLLY FANCY SHAPE

OTHER CUSTOM SYSTEMS

BLACK FOSTER CUSTOM

BRIGHT LINE

FIFTY+ CUSTOM

LARK & ACCESSORIES


LARK-111


LARK

TRIMLESS TOOL

CREDITS

ART DIRECTION
Arkoslight Team

GRAPHIC DESIGN
Estudio David Cercós

EDITION
April 2023
Copyright © Arkoslight 2023
All rights reserved

ARKOSLIGHT
Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia
Valencia · Spain
Fax +34 961 667 054
info@arkoslight.com
www.arkoslight.com

Tel. +34 961 667 207
Tel. +44 2039 66 45 92
Tel. +33 182 885 200
Tel. +39 02 9475 0007
Tel. +49 221 7159 4740

JOKERLIGHT
Arkoslight trades its products with
UL certification through Jokerlight
2750 NW 84th Ave
Doral · FL 33122 (USA)
info@jokerlight.com
www.jokerlight.com

AENOR
GESTIÓN DE LA CALIDAD
ISO 9001
ER-0148/2000

AENOR
GESTIÓN AMBIENTAL
ISO 14001
GA-2008/0547

CERTIFIED IQNet MANAGEMENT SYSTEM

ENEC 01

IEC IECEE

5Year GUARANTEE

DIALux PREMIUM PARTNER

FSC www.fsc.org
MIXTO
Papel procedente de fuentes responsables
FSC® C165484